





RELATED DOCUMENTS

SEE SPECIFICATIONS

CABLE LENGTH	TOLERANCE* + 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER	
ALL LENGTHS		
STRIP LENGTH	TOLERANCE *	
0-7mm	±0.5mm	
8-29mm	±1.0mm	
30-49mm	±2.0mm	
50-69mm	±3.0mm	
70-100mm	±4.0mm	
OVER 100mm	±5.0mm	
* UNLESS OTHERWISE SPECIFIED		

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER

SOURCE DRAWING - FOR REFERENCE ONLY

 3. 4. 	$\oplus \Box$	INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.
MATERIAL		DRFT RDS
SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	APVD J.S.
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME
FINISH	CONTACT TURCK	MILLIMETE
SEE SPECIFICATIONS	FOR MORE INFORMATION	

3RD ANGLE

PROJECTION

3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us

DATE 05/30/14 DESCRIPTION VB2P3-RS 4.4T-*/2RK 4T-*/* SCALE 1 = 1.5 (a)

(b) (c) EASUREMENT IDENTIFICATION NO. REV er [Inch] Α

DRAWING RELEASE

NOTES:

SPECIFIC LENGTHS.

RDS 09/16/15 DESCRIPTION DATE ECO NO.

DO NOT SCALE THIS DRAWING

THIS DRAWING IS CONFIDENTIAL AND THE

FILE: 777032750 SHEET 1 OF 1